Viaplant® TEXTILE

TECHNICAL DOCUMENTATION

PRODUCT NAME

Viaplant Textile with top lamination

INTRODUCTION

Immerse your space in the beauty of nature with our exquisite laminated wall panels, meticulously crafted with real preserved plant materials.

Each sheet showcases delicate vibrant petals, and textured leaves, encapsulated beneath a crystal-clear protective layer that enhances their organic charm while ensuring durability.

The intricate details of nature's artistry bring depth, warmth, and a sense of tranquility to any interior, making every wall a unique, living masterpiece.

Perfect for those who appreciate natural elegance with a modern, lasting finish.

PRODUCT DESCRIPTION

Decorative textile based material containing real plant material. It can also be laminated on a wide range of surfaces similarly to veneer.

Laminated elastomeric polymer with textile backing.

The polymer has low-temperature toughness, stress-crack resistance, waterproof properties, and resistance to UV radiation

PRODUCT SPECIFICATION*

Maximum widht: 1150mm

Maximum length: 2400mm

Weight: 980g/m2 (+/-20%)**

Thickness: 1.1 mm (+50/-20%)**

Opacity: >70%**

Non-brethable

* Specifications are subject to change without notice.

**the exact specification may vary due to chosen plant and textile material and it's density

BENEFITS AND PROPERTIES

Perfect smudge and water-resistance, soft touch

Highly resistant to wear and tear as well as resistant to abrasion

The noise-dampening nature of the bonding copolymer used gives the material sound absorbent properties

BENEFITS AND PROPERTIES

Due to the natural plant content some colors may fade with time depending on the exposure to natural or artifical lighting

Some artificial lighting and direct sunlight accelerate the fading of the plant material

Not yet certified for flame retardancy (certification in progress)

Excellent water, soap, detergent, oil and sovent resistance***

***For further information read through our FAQs or contact us directly!

KEY APPLICATION

Creative material for custom lamp shades, veneer-like decorative finish, ect.

STORAGE INSTRUCTIONS

The shelf life of this media is 3 months under normal conditions (10°C – 35°C at a relative humidity 40% - 60%).

Higher humidity and/or temperature can affect the product performance.

Always store the media in a dark place in its original packaging.

Do not bend the sheets in less than 50cm radius even temporarely.

DIRECTIONS FOR USE

Before using the media the user must examine the suitability of the media for each application.

It is recommended to adapt the material to indoor climate at least 24 hours before usage.

Because of the material's characteristics, the pattern cannot be seamlessly aligned between adjacent panels.

Since real plant materials are used in the panels, the patterns will not be uniform.

Future manufacturing batches may not perfectly match earlier produced patterns.

THERMAL LOAD RESTRICTIONS:

The product is intended for use only in normal indoor environments. The maximum permissible surface temperature of the panels is 50 °C. A minimum safety distance of at least 50 cm must be maintained from open flames and other direct heat sources. Exceeding the temperature limit or exposure to radiant heat may result in material damage (deformation, delamination).

SERVICE LIFE

We shall not assume liability for non-performance of the media.

QUALITY CHARACTERISTICS AND ACCEPTED NATURAL VARIATIONS

Due to the manufacturing technology and the inherent natural inhomogeneity of the plant components used in the composite material, the following phenomena may occur and **shall not be considered manufacturing defects:**

Presence of Foreign Materials

Maximum allowed ratio of non-plant-based foreign materials: 0.05% / m^2

Maximum allowed ratio of plant-based foreign materials: 0.10% / m^2

Plant Coverage and Uniformity

Permissible variation in plant material density between sample surface units (50×50 cm): ±20%

Surface Homogeneity

Maximum total area of acceptable surface imperfections: 0.10% / m^2

Surface Wrinkling

Surface wrinkling may occur on up to 20% of the total surface area

PHENOMENA NOT CONSIDERED AS PRODUCT DEFECTS WITHIN THE WARRANTY PERIOD

During the product's use and within the warranty period, the following changes **shall not be classified as product defects:**

Color Fading – minor fading may occur due to the natural origin of the plant material

Thermal Expansion – the composite material may react to temperature changes

Delamination (Layer Separation):

May occur along edges, cutouts, or drilled holes up to a maximum width of 20 mm

Localized delamination on the surface is permissible: 10–20 mm in diameter, with a maximum frequency of 10 instances / m^2

Localized delamination on the surface with a diameter below 10 mm is not considered a defect.

POTENTIAL MANUFACTURING VARIATIONS IN CASE OF ORDERS PLACED AT DIFFERENT TIMES

Due to the natural composition of Viaplant Flies and the seasonal and geographical variability of the plant-based raw materials, in the case **of orders placed at different times**, or subsequent repeat or supplementary orders, the following **cannot be guaranteed:**

Full availability of the plant materials used in previous production batches

Visual consistency with earlier production, including **color tone, texture, and coverage**

Identical technical specifications to previous batches

These deviations resulting from the natural raw materials **shall not be considered manufacturing defects.**

Viaplant® GLASS

Technikai információk

TULAJDONSÁGOK

Viaplant GLASS borostyánszerű, fényes, edzett üveganyag, amely közbezárja a természetes növényi összetevőket. Ellenáll a kémiai reakcióknak és a fizikai igénybevételnek.

JELLEMZŐK
fényes üvegfelület, élénk színek, az üveg bizonyos fokú mélységi hatást kölcsönöz az anyagnak

ALKALMAZÁS
Falburkolatok, korlátok, zuhanykabinok, zuhany paravánok, design radiátor előlapok, bútorok, ablakok és ajtóüvegek

TECHNIKAI ADATOK

MÉRETEK: Egyedi méret a megrendelő előre meghatározott igényei szerint, mivel az edzett üveget nem lehet utólagosan fúrni, vágni, formálni.

Maximális gyártási méretek:
• Edzett üveg: 1600x3000 mm
• Hőszigetelt üveg: 1600x3000 mm
• Ragasztott glass: 1600x3000 mm

VASTAGSÁG: 3mm-től 10 mm-ig, egy vagy két rétegű
SÚLY: mm/m2/2kg
VÍZÁLLÓSÁG: vízálló és vízlepergető; nedves környezetben a vágott élek élzárása szükséges
UV ÁLLÓSÁG: UV álló, egyhe fakulás lehetséges
KARCÁLLÓSÁG: magasfokú karcállóság, különösen az edzett üveg esetében
FIXING TECHNIQUES: similar to methods used in the glass industry (framing, special screwing, etc.)

NÖVÉNYMINTÁZATOK

Poa / fű
Rosa / rózsa
Peonia / bazsarózsa
Lilium / sásliliom
Lunaria / holdviola
Foli brun / barna levelek (a szín tónusa változó)
Eleagna / ezüstfa
Lignum colour, blue / festett fagyapot
Lignum colour, yellow / festett fagyapot
Cotinus / cserszömörce
Phragmit / nád
Triticum / szalma
Solidago / aranyvessző
Calam-poa / tippan-fű
Gramina / széna

Viaplant® VLIES

TECHNICAL DOCUMENTATION

PRODUCT NAME

Viaplant Vlies with top lamination

INTRODUCTION

Immerse your space in the beauty of nature with our exquisite laminated wall panels, meticulously crafted with real preserved plant materials.
Each sheet showcases delicate vibrant petals, and textured leaves, encapsulated beneath a crystal-clear protective layer that enhances their organic charm while ensuring durability.
The intricate details of nature's artistry bring depth, warmth, and a sense of tranquility to any interior, making every wall a unique, living masterpiece.
Perfect for those who appreciate natural elegance with a modern, lasting finish.

PRODUCT DESCRIPTION

Decorative wall covering containing real plant material.

Laminated elastomeric polymer with non-woven backing.

The polymer has low-temperature toughness, stress-crack resistance, waterproof properties, and resistance to UV radiation.

PRODUCT SPECIFICATION*

maximum widht: 1150mm

maximum length: 2400mm

Weight: 980g/m2 (+/-20%)**

Thickness: 1.1 mm (+50/-20%)**

Opacity: >98%**

non-brethable

* Specifications are subject to change without notice.

**the exact specification may vary due to chosen plant material and it's density

BENEFITS AND PROPERTIES

Perfect smudge and water-resistance, soft touch

Highly resistant to wear and tear as well as resistant to abrasion.

The noise-dampening nature of the bonding copolymer used gives the material sound absorbent properties

Due to the natural plant content some colors may fade with time depending on the exposure to natural or artifical lighting

BENEFITS AND PROPERTIES

KEY APPLICATION

Framed Wallpaper

Fixed size wallpaper / mural

STORAGE INSTRUCTIONS

The shelf life of this media is 3 months under normal conditions (10°C – 35°C at a relative humidity 40% - 60%)

Higher humidity and/or temperature can affect the product performance.

Always store the media in a dark place in its original packaging.

Do not bend the sheets in less than 50cm radius even temporarely

DIRECTIONS FOR USE

Before using the media the user must examine the suitability of the media for each application.

Paste-the-wall application, in accordance with instructions.

Use only on flat surfaces

It is recommended to adapt the material to indoor climate at least 24 hours before usage.

Use double seam cut method at application to avoid overlaps and seams

Because of the material's characteristics, the pattern cannot be seamlessly aligned between adjacent wall panels.

Since real plant materials are used in the panels, the patterns will not be uniform.

Future manufacturing batches may not perfectly match earlier produced patterns.

SERVICE LIFE

Given the wallcovering is professionally installed, the reference service life is 1 year

We shall not assume liability for non-performance of the media.